



CHEVILLEUR AERFAST M50 - code 306191

RIF. COD.

1	B000028A12	43	B000026A11	85	D450243A01
2	C450101A01	44	B000028B14	86	D450304A01
3	C450103A01	45	C450180A01	87	D750361A01
4	B000028C04	46	C750701K01	88	D450283A01
5	C450180A01	47	C750703K01		
6	D450123A01	48	C750720K01		
7	C240160A01	49	B000021C01		
8	B000020A06	50	D750484A01		
9	C450181A01	51	C750689A01		
10	B000020A45	52	B000022A01		
11	D450202A01	53	B000028E03		
12	B000020A42	54	B000026A11		
13	B000020A40	55	B000028B12		
14	D450204A01	56	B000022C01		
15	B000020A47	57	C450724K01		
16	B000023B04	58	B000028B13		
17	B000020A54	59	B000022C01		
18	C450220A01	60	B000028B04		
19	C450225K04	61	C750681K05		
20	B000020A42	62	C230661A01		
21	D450241A01	63	C750600K01		
22	B000020A41	64	B000028B20		
23	B000020A50	65	C750507A01		
24	D450243A01	66	B000028C04		
25	C450244A01	67	C750540K07		
26	B000020B02	68	D450984K02		
27	B000020B01	69	B000023C01		
28	B000020A02	70	C275801K01		
29	D450304A01	71	D450871K01		
30	B000020B11	72	C275843K01		
31	B000020A02	73	B000028A13		
32	D750361A01	74	C450944K01		
33	B000020A19	75	C450942K01		
34	B000020A19	76	C450943K01		
35	B000026A12	77	C450746K01		
36	D750411A02	78	C450747K01		
37	C450262A01	79	B000028B01		
38	B000020A42	80	D450123A01		
39	D450283A01	81	D450202A01		
40	C650261K01	82	D450204A01		
41	C750500A02	83	D450226K04		
42	D750441A01	84	D450241A01		

Code **A750000K05**  
 Model **M50**  
 Staple type **PINS**  
 Min. length **25 mm.**  
 Max. length **50 mm.**

Code **A750000K05**  
 Modèle **M50**  
 Agrafe type **PINS**  
 Longueur min. **25 mm.**  
 Longueur max. **50 mm.**

TECHNICAL FEATURES

Weight: **2580 gr.**  
 Dimensions: **86-268-368 mm.**  
 Air consumption: **1,98 NI/shot (6 bar)**  
 Min.working pressure: **4,0 bar**  
 Max.working pressure: **7,0 bar**

DONNEES TECHNIQUES

Poids: **2580 gr.**  
 Dimensions: **86-268-368 mm.**  
 Consommation d'air: **1,98 NI/coup (6 bar)**  
 Pression de fonction min.: **4,0 bar**  
 Pression de fonction max.: **7,0 bar**

NOISE POWER

EEC DIRECTIVE 89/392  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **89,4 (dB)**  
 LpA 60S 1M= **88,7 (dB)**

PUISSANCE ACOUSTIQUE

DIRECTIVE CEE 89/392  
 prEN 12549 (1999)  
 UNI EN ISO 3744 (1997)  
 LwA= **89,4 (dB)**  
 LpA 60S 1M= **88,7 (dB)**

TOOL RELATED VIBRATION

VALUE  
 EEC DIRECTIVE 89/392  
 ISO/FDIS 8662-11 (1999)  
 an.w.3s= **2,8 (m/s<sup>2</sup>)**

VALEUR DES VIBRATIONS

PAR LA MACHINE  
 DIRECTIVE CEE 89/392  
 ISO/FDIS 8662-11 (1999)  
 ah.w.3s= **2,8 (m/s<sup>2</sup>)**

B650040K01 O-Ring Kit

750/0 K05/01 08/01